

## Leaf Spring Axle Order Form (500 - 8,000 LB Capacity)

Axis Trailer Products, Inc. • Elkhart, IN. • Phone 574.264.7955 • Fax 574.266.83 3 3 • axistrailer products.com

Customer:		
Address:		
City:	State:	
Phone:		
Fax:		
Trailer Manufacturer:		
Trailer Make:		
Trailer Model:		
Capacity:  Axle Type: Str.  Axle w/Brake Flange:  Camber: Yes  Hub Face Dimension: (see  Spring Center: (see drawing)  Mount Type: (see drawing)	aight Drop Yes s No e drawing)	□ No
	d) [dler	Disc
Wheel Stud Size: 7k w	Jni-Servo 🔲 Hy	ydraulic w/Duo-Servo 2" 🔲 9/16" 🔲 5/8"
☐ Hydraulic w/U Wheel Stud Size: 7k w/	Jni-Servo Hy/8-bolt 1/2/8-bolt 9/2 No Ultrulube Galvanized	rdraulic w/Duo-Servo 2"
Hydraulic w/U Wheel Stud Size: 7k w/ 8k w/ Pre-wired: Yes Lubrication: Grease Paint: Paint  Notes:	Jni-Servo Hy /8-bolt 1/2 /8-bolt 9/ No Ultrulube Galvanized	vdraulic w/Duo-Servo 2"
Hydraulic w/U Wheel Stud Size: 7k w, 8k w,  Pre-wired: Yes Lubrication: Grease Paint: Paint	Jni-Servo Hy /8-bolt 1/2 /8-bolt 9/ No Ultrulube Galvanized	rdraulic w/Duo-Servo 2"

\*\*\*For BEAM ONLY orders - Do not complete shaded section\*\*\*

Hub Face and Spring measurements are only available in 1/4"

		Overhang	
Axle Type	Tube Size	Minimum	Maximum
T20 Idler	1 3/4"	10"	15 1/4"
T20 Brake	1 3/4"	11 ¾"	15 1/4"
T20 Idler	2 3/8"	11 ¾"	20"
T20 Brake	2 3/8"	11 ¾"	20"
T35 Straight	2 3/8"	11 1/4"	17"
D35 Drop	2 3/8"	14 %"	19"
T35 Straight	3"	14 1/4"	23"
D35 Drop	3"	14 1/4"	23"
T44 Straight	3"	14"	22"
T52/T60 Straight	3"	13"	18"
T70 Straight	3"	13"	19 1/2"
D52/D60 Drop	3"	17"	20 ½"
D70 Drop	3"	17"	19 1/2"
T80 Straight 12" x 3 %"	3 1/2"	17"	22"
D80 Drop 12" x 3 %"	3 1/2"	18"	23 ½"
ST80 Straight 12" x 2"	3 1/2"	15"	22"
DR80 Drop 12" x 2"	3 1/2"	18"	23 ½"

Hub Face and Spring measurements are only available in  $\frac{1}{4}$ " increments. More detailed axle information can be found in the Axis product catalog.

## Straight Axle



## Drop Center Axle




## **Drop Axle**



440

500 - 2,000



500 - 3,500

\*\*500# - 2000# ONLY
(Please see diagram for measurement directions)



655

6 Lug 10" and 12"



5,200 - 8,000