

10k - 12k - 16k - Axle Order Form

(10,000 - 16,000 LB Capacity)

axistrailerproducts.com 574.264.7955

*****For BEAM ONLY orders - Do not complete shaded section*****

Date: _____

Customer: _____

Address: _____

City: _____ State: _____ Zip: _____

Phone: _____

Fax: _____

Trailer Manufacturer: _____

Trailer Make: _____

Trailer Model: _____

Capacity: _____

Hub Face Dimension: (see drawing) _____

Track Width Dimension: (see drawing) _____

Spring Center: (see drawing) _____

Mount Type: (see drawing) Bottom Top

Adjustable Spring Pads: Yes No

Spring Width: 2 1/2" 3"

Spring Length: _____

Hub Bolt Pattern: (if desired) _____

Hub Pilot: 4.75 4.88

Brake Type: (if desired) Idler Electric Air
 Hydraulic Drum Hydraulic Disc

Wheel Nut: Swivel Flange Nuts Double Cap Nuts
 Tension Ring w/Cone Nuts

If Air Brake, choose air chamber: Type 20
 Type 24 Type 20/24 Type 24/24

ABS: Yes No

Pre-wired: Yes No

Lubrication: Grease Oil Bath

Paint: Paint Galvanized E-Coat Raw

Notes: _____

Customer PO: _____

Quantity: _____

Customer Signature: _____

Axle Type	Tube Size	Spindle	Track		Overhang	
			Minimum	Maximum	Minimum	Maximum
10k Spring	3 1/2"	Elec/Hyd	63"	96"	25"	31"
10k Spring	5"	Elec/Hyd	63"	96"	25"	31"
10k Spring	5"	Air Brake	70"	96"	26"	40"
12k Spring	5"	Elec/Hyd	63"	96"	26"	32"
12k Spring	5"	Air Brake	70"	96"	26"	40"
16k Spring	5"	Elec/Hyd	63"	96"	26"	32"
16k Spring	5"	Air Brake	70"	96"	26"	36"

Hub Face and Spring measurements are only available in 1/4" increments. More detailed axle information can be found in the AL-KO Axis product catalog.



(10 Lug uses 3/4" wheel stud)

